

OM SENI

TPESD5681N07

1-Line Uni- directional TVS Diode

Features

- Ultra small package: 1.0x0.6x0.5mm
- Ultra low capacitance: 150pF typical
- Ultra low leakage: nA level
- Low operating voltage: 7V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
 - – IEC 61000-4-2 (ESD) immunity test
Air discharge: $\pm 30\text{kV}$
Contact discharge: $\pm 30\text{kV}$
 - – IEC61000-4-5 (Lightning) 27A (8/20 μs)
- RoHS Compliant
- Lead Finish: NiPdAu

Mechanical Characteristics

- Package: DFN1006-2 (0402)
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- Moisture Sensitivity: Level 3 per J-STD-020
- Terminal Connections: See Diagram Below


Applications

- Cellular Handsets and Accessories
- Personal Digital Assistants
- Notebooks and Handhelds
- Portable Instrumentation
- Digital Cameras
- Peripherals

Ordering Information

Part Number	Qty per Reel	Reel Size
TPESD5681N07	10000	7"

Dimensions and Pin Configuration



Marking : LB Or 07

OM SENI

Absolute Maximum Ratings (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μs)	Ppk	480	W
Peak Pulse Current (8/20μs)	Ipp	27	A
ESD per IEC 61000-4-2 (Air)	VESD	±30	kV
ESD per IEC 61000-4-2 (Contact)		±30	
Operating Temperature Range	TJ	-55 to +125	°C
Storage Temperature Range	Tstg	-55 to +150	°C

Electrical Characteristics (TA=25°C unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	VRWM			7	V	
Breakdown Voltage	VBR	8	9.5	10	V	IT = 1mA
Reverse Leakage Current	IR			0.5	uA	VRWM = 7V
Clamping Voltage	VC		12		V	Ipp=10A(8x 20us pulse)
Clamping Voltage	VC			18	V	Ipp=27A(8x 20us pulse)
Junction Capacitance	CJ		150		pF	VR = 0V, f = 1MHz

OM SENI

Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)

Fig1. 8/20 μs Pulse Waveform




Fig2. ESD Pulse Waveform (according to IEC 61000-4-2)




Fig3. Power Derating Curve





Figure 4: ESD Clamping (8kV Contact per IEC 61000-4-2)



OM SENI

Ordering Information

PREFERRED P/N	PACKAGE	SIZE(mm)	DELIVERY MODE	MPQ(PCS)
	DFN1006-2L	1.00×0.60×0.37	7" REEL	10,000

Recommended Soldering Conditions



Package Outline Dimensions (DFN1006-2L)

Symbol	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
A	0.950	1.050	0.037	0.041
B	0.550	0.650	0.022	0.026
C	0.350	0.450	0.014	0.018
D	0.550	0.650	0.022	0.026
D ₁	0.280	0.380	0.011	0.015
E	0.450	0.550	0.018	0.022
L	0.000	0.100	0.000	0.004

Suggested Pad Layout

Symbol	Dimensions			
	Millimeters		Inches	
	Min	Max	Min	Max
J	0.50	0.60	0.020	0.024
K	0.25	0.35	0.010	0.014
M	0.55	0.65	0.022	0.026