www.omseni.com

OM SENI

MJD41CT4G (NPN),
MJD42CT4G (PNP)
Complementary Power Transistors

DPAK for Surface Mount Applications

Designed for general purpose amplifier and low speed switching applications.

Features

- Lead Formed for Surface Mount Applications in Plastic Sleeves (No Suffix)
- Straight Lead Version in Plastic Sleeves ("1" Suffix)
- Electrically Similar to Popular TIP41 and TIP42 Series
- Epoxy Meets UL 94 V−0 @ 0.125 in
- These Devices are Pb−Free and are RoHS Compliant

MAXIMUM RATINGS

Rating	Symbol	Max	Unit
Collector−Emitter Voltage	V_{CEO}	100	Vdc
Collector−Base Voltage	V_{CB}	100	Vdc
Emitter−Base Voltage	V_{EB}	5	Vdc
Collector Current − Continuous	I_C	6	Adc
Collector Current − Peak	I_{CM}	10	Adc
Base Current	I_B	2	Adc
Total Power Dissipation @ T_C = 25°C Derate above 25°C	P_D	 20 0.16	W W/°C
Total Power Dissipation (Note 1) @ T_A = 25°C Derate above 25°C	P_D	 1.75 0.014	W W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−65 to +150	°C
ESD − Human Body Model	HBM	3B	V
ESD − Machine Model	MM	C	V

SILICON
POWER TRANSISTORS
6 AMPERES
100 VOLTS, 20 WATTS

COMPLEMENTARY





DPAK
CASE 369C
STYLE 1

MARKING DIAGRAMS



DPAK

A = Assembly Location
Y = Year
WW = Work Week
J4xC = Device Code
x = 1 or 2
G = Pb−Free Package

OM SENI

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	6.25	°C/W
Thermal Resistance, Junction−to−Ambient (Note 2)	$R_{\theta JA}$	71.4	°C/W

2. These ratings are applicable when surface mounted on the minimum pad sizes recommended.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector−Emitter Sustaining Voltage (Note 3) (I_C = 30 mAdc, I_B = 0)	$V_{CEO(sus)}$	100	–	Vdc
Collector Cutoff Current (V_{CE} = 60 Vdc, I_B = 0)	I_{CEO}	–	50	μAdc
Collector Cutoff Current (V_{CE} = 100 Vdc, V_{EB} = 0)	I_{CES}	–	10	μAdc
Emitter Cutoff Current (V_{BE} = 5 Vdc, I_C = 0)	I_{EBO}	–	0.5	mAdc
ON CHARACTERISTICS (Note 3)				
DC Current Gain (I_C = 0.3 Adc, V_{CE} = 4 Vdc) (I_C = 3 Adc, V_{CE} = 4 Vdc)	h_{FE}	 30 15	 – 75	–
Collector−Emitter Saturation Voltage (I_C = 6 Adc, I_B = 600 mAdc)	$V_{CE(sat)}$	–	1.5	Vdc
Base−Emitter On Voltage (I_C = 6 Adc, V_{CE} = 4 Vdc)	$V_{BE(on)}$	–	2	Vdc
DYNAMIC CHARACTERISTICS				
Current Gain − Bandwidth Product (Note 4) (I_C = 500 mAdc, V_{CE} = 10 Vdc, f_{test} = 1 MHz)	f_T	3	–	MHz
Small−Signal Current Gain (I_C = 0.5 Adc, V_{CE} = 10 Vdc, f = 1 kHz)	h_{fe}	20	–	–

3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
4. $f_T = |h_{fe}| \bullet f_{test}$.

www.omseni.com

OM SENI

TYPICAL CHARACTERISTICS



Figure 1. Power Derating



R_B and R_C VARIED TO OBTAIN DESIRED CURRENT LEVELS
D_1 MUST BE FAST RECOVERY TYPE, e.g.:
MSB5300 USED ABOVE $I_B \approx$ 100 mA
MSD6100 USED BELOW $I_B \approx$ 100 mA
REVERSE ALL POLARITIES FOR PNP.

Figure 2. Switching Time Test Circuit



Figure 3. DC Current Gain



Figure 4. Turn−On Time



Figure 5. “On” Voltages



Figure 6. Turn−Off Time

OM SENI



Figure 7. Collector Saturation Region



Figure 8. Capacitance



Figure 9. Thermal Response



Figure 10. Maximum Forward Bias Safe Operating Area

There are two limitations on the power handling ability of a transistor: average junction temperature and second breakdown. Safe operating area curves indicate $I_C - V_{CE}$ limits of the transistor that must be observed for reliable operation; i.e., the transistor must not be subjected to greater dissipation than the curves indicate.

The data of Figure 10 is based on $T_{J(pk)} = 150°C$; T_C is variable depending on conditions. Second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(pk)} \leq 150°C$. $T_{J(pk)}$ may be calculated from the data in Figure 9. At high case temperatures, thermal limitations will reduce the power that can be handled to values less than the limitations imposed by second breakdown.

OM SENI

Ordering Information

PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
TO-252	R3	0.305	2500	5000	25000	13''

Package Outline Dimensions (TO-252)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A2	0.90	1.10	0.035	0.043
b	0.66	0.86	0.026	0.034
b1	5.10	5.46	0.201	0.215
b2	4.27	4.37	0.168	0.172
b3	0.78	0.90	0.031	0.035
c	0.45	0.55	0.018	0.022
D	5.90	6.30	0.232	0.248
D1	5.35 REF.		0.211REF.	
E	6.30	6.70	0.248	0.264
E1	4.83 REF.		0.190 REF.	
e	2.18	2.38	0.086	0.094
H	9.80	10.4	0.386	0.409
L1	2.70	3.10	0.106	0.122
L3	0.80	1.20	0.031	0.047
L4	0.60	1.00	0.024	0.039
L5	1.8 REF.		0.071 REF.	
L6	-	0.12	-	0.005

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
a	3.70	-	0.146	-
b	4.37	-	0.172	-
X	-	5.80	-	0.228
X1	-	1.20	-	0.047
Y	-	5.85	-	0.230
Y1	-	2.00	-	0.079