
www.omseni.com

OM SENI

MMSD459A
Small Signal Diode



SOD123
Color Band Denotes Cathode
Top Marking: 22

Absolute Maximum Ratings* T_A = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V_{RRM}	Maximum Repetitive Reverse Voltage	100	V
$I_{F(AV)}$	Average Rectified Forward Current	200	mA
I_{FSM}	Non-repetitive Peak Forward Surge Current Pulse Width = 1.0 second Pulse Width = 1.0 microsecond	 1.0 4.0	 A A
T_{STG}	Storage Temperature Range	-55 to +150	°C
T_J	Operating Junction Temperature	150	°C

* These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES:
1) These ratings are based on a maximum junction temperature of 200 degrees C.
2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics

Symbol	Parameter	Value	Units
P_D	Power Dissipation	400	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	312	°C/W

Electrical Characteristics T_A = 25°C unless otherwise noted


Symbol	Parameter	Test Conditions	Min.	Max.	Units
V_R	Breakdown Voltage	I_R = 100μA	200		V
V_F	Forward Voltage	I_F = 100mA		1.0	V
I_R	Reverse Leakage	V_R = 175V V_R = 175V, T_A = 150°C		25 5.0	nA μA
C_T	Total Capacitance	V_R = 0, f = 1.0MHz		6.0	pF

OM SENI

Ordering Information


PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOD-123	R1	0.012	3000	30000	240000	7''

Package Outline Dimensions (SOD-123)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	3.55	3.85	0.140	0.152
B	2.55	2.85	0.100	0.112
C	1.40	1.80	0.055	0.071
D	0.95	1.35	0.140	0.152
E	0.51	0.71	0.037	0.053
F	-	0.15	-	0.006
G	0.15	0.45	0.006	0.008
H	0.08	0.25	0.003	0.010
θ	-	8°	-	8°

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	0.91	-	0.036	-
K	-	2.36	-	0.092
M	1.22	-	0.048	-