www.omseni.com

OM SENI

NCP785A
Linear Regulator - Wide Input Voltage Range, Ultra-Low Iq, High PSRR
10 mA

The NCP785A is a high−performance linear regulator, offering a very wide operating input voltage range of up to 450 V DC, with an output current of up to 10 mA.

Ideal for high input voltage applications such as industrial and home metering, home appliances. The NCP785A family offers ±5% initial accuracy, extremely high−power supply rejection ratio and ultra−low quiescent current. The NCP785A is optimized for high−voltage line and load transients, making this part ideal for harsh environment applications.

The NCP785A is offered in fixed output voltage options 3.3 V, 5.0 V, 12 V and 15 V.

SOT−89 package offers good thermal performance and help to minimize the solution size.



SOT−89
CASE 528AG

MARKING DIAGRAM



(Top Views)
(Tab is connected to Pin 2)

A = Assembly Location
Y = Year
W = Work Week
XXXXX = Specific Device Code
▪ = Pb−Free Package

(Note: Microdot may be in either location)

Features

- Wide Input Voltage Range:
  DC: Up to 450 V
  AC: 85 V to 260 V (half−wave rectifier and 2.2 μF capacitor)
- 10 mA Guaranteed Output Current
- Ultra Low Quiescent Current: Typ. 10 μA ($V_{OUT} \leq 5$ V)
- ±5% Accuracy Over Full Load, Line and Temperature Variations
- Ultra−high PSRR: 70 dB at 60 Hz, 90 dB at 100 kHz
- Stable with Ceramic Output Capacitor 22 μF MLCC
- Thermal Shutdown and Current Limit Protection
- Available in Thermally Enhanced SOT89−3 Package
- This is a Pb−Free Device

Typical Applications

- Industrial Applications, Home Appliances
- Home Metering / Network Application
- Off−line Power Supplies



Figure 1. Typical Applications

OM SENI



Figure 2. Simplified Internal Block Diagram

Table 1. PIN FUNCTION DESCRIPTION

Pin No. (SOT−89)	Pin Name	Description
1	VIN	Supply Voltage Input. Connect 2.2 μF capacitor from VIN to GND.
2, Tab	GND	Ground connection.
3	VOUT	Regulator Output. Connect 22 μF or larger MLCC capacitor from VOUT to GND.

Table 2. ABSOLUTE MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Input Voltage (Note 1)	V_{IN}	−0.3 to 700	V
Output Voltage	V_{OUT}	−0.3 to 18	V
Maximum Junction Temperature	$T_{J(MAX)}$	150	°C
Storage Temperature	T_{STG}	−55 to 150	°C
ESD Capability, Human Body Model (All pins except HV pin no.1) (Note 2)	ESD_{HBM}	2000	V
ESD Capability, Machine Model (Note 2)	ESD_{MM}	200	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Peak 650 V max 1 ms non repeated for 1 s
2. This device series incorporates ESD protection and is tested by the following methods:

Rating	Symbol	Value	Unit
Thermal Characteristics, SOT−89 Thermal Resistance, Junction−to−Air	$R_{\theta JA}$	79	°C/W

OM SENI

Table 4. ELECTRICAL CHARACTERISTICS, V_{OUT} = 3.3 V (−40°C ≤ T_J ≤ 85°C; V_{IN} = 340 V; I_{OUT} = 100 μA, C_{IN} = 2.2 μF, C_{OUT} = 22 μF, unless otherwise noted. Typical values are at T_J = +25°C.) (Note 3)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage DC		V_{IN}	25		450	V
Output Voltage Accuracy	T_J = 25°C, Iout = 100 μA, 25 V ≤ Vin ≤ 450 V	V_{OUT}	3.1515	3.3	3.4485	V
	−40°C ≤ T_J ≤ 85°C, Iout = 100 μA, 25 V ≤ Vin ≤ 450 V	V_{OUT}	3.135	3.3	3.465	V
Line Regulation	25 V ≤ Vin ≤ 450 V, Iout = 100 μA	Reg_{LINE}	−0.5	0.2	+0.5	%
Load Regulation	100 μA ≤ I_{OUT} ≤ 10 mA, Vin = 35 V	Reg_{LOAD}	−1.0	0.6	+1.0	%
Maximum Output Current (Note 4)	35 V ≤ Vin ≤ 450 V	I_{OUT}	10.5			mA
Quiescent Current	I_{OUT} = 0, 25 V ≤ Vin ≤ 450 V	I_Q		7.5	14	μA
Ground Current (Note 4)	25 V ≤ Vin ≤ 450 V 0 < I_{OUT} ≤ 10 mA	I_{GND}			15	μA
Power Supply Rejection Ratio	Vin = 340 V_{DC} +1 Vpp modulation, Iout = 100 μA, f = 1 kHz	PSRR		70		dB
Noise	f = 100 Hz to 100 kHz Vin = 340 V_{DC}, Iout = 100 μA	V_{NOISE}		240		μVrms
Thermal Shutdown Temperature (Note 5)	Temperature increasing from T_J = +25°C	T_{SD}		145		°C
Thermal Shutdown Hysteresis (Note 5)	Temperature falling from T_{SD}	T_{SDH}	–	10	–	°C

Table 5. ELECTRICAL CHARACTERISTICS, V_{OUT} = 5.0 V (−40°C ≤ T_J ≤ 85°C; V_{IN} = 340 V; I_{OUT} = 100 μA, C_{IN} = 2.2 μF, C_{OUT} = 22 μF, unless otherwise noted. Typical values are at T_J = +25°C.) (Note 3)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage DC		V_{IN}	50		450	V
Output Voltage Accuracy	T_J = 25°C, Iout = 100 μA, 50 V ≤ Vin ≤ 450 V	V_{OUT}	4.775	5.0	5.225	V
	−40°C ≤ T_J ≤ 85°C, Iout = 100 μA, 50 V ≤ Vin ≤ 450 V	V_{OUT}	4.75	5.0	5.25	V
Line Regulation	50 V ≤ Vin ≤ 450 V, Iout = 100 μA	Reg_{LINE}	−0.5	0.2	+0.5	%
Load Regulation	100 μA ≤ I_{OUT} ≤ 10 mA, Vin = 55 V	Reg_{LOAD}	−1.0	0.62	+1.0	%
Maximum Output Current (Note 4)	55 V ≤ Vin ≤ 450 V	I_{OUT}	10.5			mA
Quiescent Current	I_{OUT} = 0, 50 V ≤ Vin ≤ 450 V	I_Q		16	21	μA
Ground Current (Note 4)	50 V ≤ Vin ≤ 450 V 0 < I_{OUT} ≤ 10 mA	I_{GND}			23	μA
Power Supply Rejection Ratio	Vin = 340 V_{DC} +1 Vpp modulation, Iout = 100 μA, f = 1 kHz	PSRR		70		dB
Noise	f = 100 Hz to 100 kHz Vin = 340 V_{DC}, Iout = 100 μA	V_{NOISE}		300		μVrms
Thermal Shutdown Temperature (Note 5)	Temperature increasing from T_J = +25°C	T_{SD}		145		°C
Thermal Shutdown Hysteresis (Note 5)	Temperature falling from T_{SD}	T_{SDH}	–	10	–	°C

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at T_J = T_A = 25°C. Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.
4. A proper heatsinking and/or low duty cycle pulse techniques are used to operate the device within the Safe Operating Area.
5. Guaranteed by design

www.omseni.com

OM SENI

Table 6. ELECTRICAL CHARACTERISTICS, V_{OUT} = 12 V ($-40°C \le T_J \le 85°C$; V_{IN} = 340 V; I_{OUT} = 100 μA, C_{IN} = 2.2 μF, C_{OUT} = 22 μF, unless otherwise noted. Typical values are at T_J = +25°C.) (Note 6)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage DC		V_{IN}	55		450	V
Output Voltage Accuracy	T_J = 25°C, Iout = 100 μA, 55 V ≤ Vin ≤ 450 V	V_{OUT}	11.460	12	12.540	V
	−40°C ≤ T_J ≤ 85°C, Iout = 100 μA, 55 V ≤ Vin ≤ 450 V	V_{OUT}	11.4	12	12.6	V
Line Regulation	55 V ≤ Vin ≤ 450 V, Iout = 100 μA	Reg_{LINE}	−0.5	0.1	+0.5	%/V
Load Regulation	100 μA ≤ I_{OUT} ≤ 10 mA, Vin = 65 V	Reg_{LOAD}	−1.0	0.66	+1.0	%
Maximum Output Current (Note 7)	55 V ≤ Vin ≤ 450 V	I_{OUT}	10.5			mA
Quiescent Current	I_{OUT} = 0, 55 V ≤ Vin ≤ 450 V	I_Q		17	22	μA
Ground Current (Note 7)	55 V ≤ Vin ≤ 450 V 0 < I_{OUT} ≤ 10 mA	I_{GND}			25	μA
Power Supply Rejection Ratio	Vin = 340 V_{DC} +1 Vpp modulation, Iout = 100 μA, f = 1 kHz	PSRR		70		dB
Noise	f = 100 Hz to 100 kHz Vin = 340 V_{DC}, Iout = 100 μA	V_{NOISE}		420		μVrms
Thermal Shutdown Temperature (Note 8)	Temperature increasing from T_J = +25°C	T_{SD}		145		°C
Thermal Shutdown Hysteresis (Note 8)	Temperature falling from T_{SD}	T_{SDH}	–	10	–	°C

Table 7. ELECTRICAL CHARACTERISTICS, V_{OUT} = 15 V ($-40°C \le T_J \le 85°C$; V_{IN} = 340 V; I_{OUT} = 100 μA, C_{IN} = 2.2 μF, C_{OUT} = 22 μF, unless otherwise noted. Typical values are at T_J = +25°C.) (Note 6)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Operating Input Voltage DC		V_{IN}	60		450	V
Output Voltage Accuracy	T_J = 25°C, Iout = 100 μA, 60 V ≤ Vin ≤ 450 V	V_{OUT}	14.325	15	15.675	V
	−40°C ≤ T_J ≤ 85°C, Iout = 100 μA, 60 V ≤ Vin ≤ 450 V	V_{OUT}	14.25	15	15.75	V
Line Regulation	60 V ≤ Vin ≤ 450 V, Iout = 100 μA	Reg_{LINE}	−0.5	0.1	+0.5	%/V
Load Regulation	100 μA ≤ I_{OUT} ≤ 10 mA, Vin = 65 V	Reg_{LOAD}	−1.0	0.66	+1.0	%
Maximum Output Current (Note 7)	65 V ≤ Vin ≤ 450 V	I_{OUT}	10.5			mA
Quiescent Current	I_{OUT} = 0, 60 V ≤ Vin ≤ 450 V	I_Q		18	22	μA
Ground Current (Note 7)	60 V ≤ Vin ≤ 450 V 0 < I_{OUT} ≤ 10 mA	I_{GND}			25	μA
Power Supply Rejection Ratio	Vin = 340 V_{DC} +1 Vpp modulation, Iout = 100 μA, f = 1 kHz	PSRR		70		dB
Noise	f = 100 Hz to 100 kHz Vin = 340 V_{DC}, Iout = 100 μA	V_{NOISE}		500		μVrms
Thermal Shutdown Temperature (Note 8)	Temperature increasing from T_J = +25°C	T_{SD}		145		°C
Thermal Shutdown Hysteresis (Note 8)	Temperature falling from T_{SD}	T_{SDH}	–	10	–	°C

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

6. Performance guaranteed over the indicated operating temperature range by design and/or characterization production tested at $T_J = T_A$ = 25°C. Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.
7. A proper heatsinking and/or low duty cycle pulse techniques are used to operate the device within the Safe Operating Area.
8. Guaranteed by design

OM SENI

TYPICAL CHARACTERISTICS



Figure 3. Output Voltage vs. Temperature



Figure 4. Output Voltage vs. Temperature



Figure 5. Output Voltage vs. Temperature



Figure 6. Output Voltage vs. Temperature



Figure 7. Output Voltage vs. Input Voltage



Figure 8. Output Voltage vs. Input Voltage

OM SENI

TYPICAL CHARACTERISTICS



Figure 9. Output Voltage vs. Input Voltage



Figure 10. Output Voltage vs. Input Voltage



Figure 11. Quiescent Current vs. Input Voltage



Figure 12. Quiescent Current vs. Input Voltage

www.omseni.com

TYPICAL CHARACTERISTICS



Figure 13. Quiescent Current vs. Input Voltage



Figure 14. Quiescent Current vs. Input Voltage



Figure 15. Output Voltage vs. Output Current



Figure 16. Output Voltage vs. Output Current



Figure 17. Output Voltage vs. Output Current



Figure 18. Output Voltage vs. Output Current

OM SENI

TYPICAL CHARACTERISTICS



Figure 19. Output Noise Density vs. Frequency



Figure 20. Output Noise Density vs. Frequency



Figure 21. Output Noise Density vs. Frequency



Figure 22. Output Noise Density vs. Frequency

www.omseni.com

APPLICATION INFORMATION

The typical application circuit for the NCP785A device is shown below.



Figure 23. Typical Application Schematic

Input Decoupling (C1)

A 1 μF capacitor either ceramic or electrolytic is recommended and should be connected close to the input pin of NCP785A. Higher value 2.2 μF is necessary to sustain the required minimum input voltage at full load for AC voltage as low as 85 V with half wave rectifier.

Output Decoupling (C2)

The NCP785A Regulator does not require any specific Equivalent Series Resistance (ESR). Thus capacitors exhibiting ESRs ranging from a few mΩ up to 0.5 Ω can be used safely. The minimum decoupling value is 22 μF. The regulator accepts ceramic chip capacitors as well as tantalum devices or low ESR electrolytic capacitors. Larger values improve noise rejection and load transient response.

Layout Recommendations

Please be sure the V_{IN} and GND lines are sufficiently wide. When the impedance of these lines is high, there is a chance to pick up noise or to cause the malfunction of regulator.

Set external components, especially the output capacitor, as close as possible to the circuit, and make leads as short as possible.

Thermal

As power across the NCP785A increases, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design layout and used package. Mounting pad configuration on the PCB, the board material, and also the ambient temperature affect the rate of temperature rise for the part. This is stating that when the NCP785A has good thermal conductivity through the PCB, the junction temperature will be relatively low with high power dissipation applications.

ORDERING INFORMATION

Part Number	Output Voltage	Marking	Package	Shipping†
NCP785AH33T1G	3.3 V	AA	SOT−89 (Pb−Free)	1000 / Tape & Reel
NCP785AH50T1G	5 V	AC		
NCP785AH120T1G	12 V	AJ		
NCP785AH150T1G	15 V	AD		

OM SENI

Ordering Information

Package	Package Code	Unit Weight(g)	Reel(pcs)	Box(pcs)	Carton(pcs)	Delivery Mode	MSL
SOT-89	R1	0.045	1000	8000	48000	7''	3
SOT-223	R3	0.231	3000	6000	30000	13''	3

Package Outline Dimensions (SOT-223)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	-	1.8	-	0.071
A1	0.020	0.100	0.001	0.004
A2	1.50	1.700	0.059	0.067
b	0.660	0.840	0.026	0.033
b1	2.900	3.100	0.114	0.122
c	0.230	0.350	0.009	0.014
D	6.300	6.700	0.248	0.264
E	6.700	7.300	0.264	0.287
E1	3.300	3.700	0.130	0.146
e	2.300(BSC)		0.091TYP	
L	0.750	-	0.030	-
θ	0°	10°	0°	10°

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	3.20	3.60	0.126	0.142
K	1.40	1.80	0.055	0.071
M	5.90	6.30	0.23	0.25
N	2.15	2.45	0.085	0.096
O	0.60	0.85	0.024	0.033

Package Outline Dimensions (SOT-89)



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.40	4.60	0.173	0.181
B	1.35	1.83	0.053	0.072
C	3.75	4.25	0.148	0.167
D	2.29	2.60	0.090	0.102
E	2.95	3.05	0.116	0.120
a	0.35	0.48	0.014	0.019
b	0.40	0.56	0.016	0.022
L	0.80	1.20	0.031	0.047
G	0.35	0.44	0.014	0.017
H	1.40	1.60	0.055	0.063

Suggested Pad Layout



Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
c	0.80	1.00	0.032	0.04
d	1.30	1.50	0.052	0.060
e	0.70	0.90	0.028	0.036
J	1.80	2.00	0.072	0.080
K	1.40	1.60	0.056	0.064
X	2.50	2.70	0.100	0.108
X1	1.30	1.50	0.052	0.060
Y	4.30	4.50	0.172	0.180
Y1	3.10	3.30	0.124	0.132
θ	-	45°	-	45°