

OM SENI

SOD-123 Surface Mount Schottky Barrier Rectifier

Features

- $V_R=40V/30/20V$
- $I_{F(AV)}=0.35A$
- For use in low voltage, high frequency inverters
- Free wheeling, and polarity protection applications

Applications


The device is a single rectifier offering low VF and excellent high temperature stability.

Mechanical Data

- Case: SOD-123
- Molding compound meets UL 94V-0 flammability rating, RoHS-compliant, halogen-free
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity: Cathode line denotes the cathode end

Function Diagram

Marking:
SD103AW:S4
SD103BW:S5
SD103CW:S6



SD103AW THRU SD103CW

Reverse Voltage
40/30/20 V

Forward Current
0.35 Ampere



Maximum Ratings (Ta=25°C Unless otherwise specified)





PARAMETER	SYMBOL	UNIT	SD103AW	SD103BW	SD103CW
Maximum repetitive peak reverse voltage	V_{RRM}	V	40	30	20
Maximum RMS voltage	V_{RMS}	V	28	21	18
Maximum DC blocking voltage	V_{DC}	V	40	30	20
Maximum Average Forward Rectified Current	$I_{F(AV)}$	mA	350		
Non-repetitive Peak Forward Surge Current @t=8.3ms Half-sine wave	I_{FSM}	A	2.0		
Power Dissipation	P_D	mW	400		
Junction temperature	T_J	°C	125		
Storage temperature range	T_{STG}	°C	-55-+150		
Typical thermal resistance	$R_{\theta JA}$	°C/W	250		

OM SENI

Electrical Characteristics (Ta=25°C Unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	UNIT	SD103AW	SD103BW	SD103CW
Maximum forward voltage	$I_F=20\text{mA}$	V_F	V	0.37		
	$I_F=200\text{mA}$	V_F		0.60		
Maximum reverse current	$V_R=30\text{V}$	I_R	μA	5.0		
	$V_R=20\text{V}$			5.0		
	$V_R=10\text{V}$			5.0		
Capacitance between terminals	$V_R = 0\text{V}, f = 1\text{MHz}$	C_T	pF	50		
Reverse Recovery time	$I_F=I_R=200\text{mA}$ $I_r=0.1 \times I_R, R_L=100\Omega$	t_{rr}	ns	10		

Ratings And Characteristics Curves (Ta=25°C Unless otherwise specified)



OM SENI

Ordering Information

PACKAGE	PACKAGE CODE	UNIT WEIGHT(g)	REEL(pcs)	BOX(pcs)	CARTON(pcs)	DELIVERY MODE
SOD-123	R1	0.012	3000	45000	180000	7"

Package Outline Dimensions (SOD-123)

Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	3.55	3.85	0.140	0.152
B	2.55	2.85	0.100	0.112
C	1.40	1.80	0.055	0.071
D	0.95	1.35	0.140	0.152
E	0.51	0.71	0.037	0.053
F	-	0.15	-	0.006
G	0.15	0.45	0.006	0.008
H	0.08	0.25	0.003	0.010
θ	-	8°	-	8°

Symbol	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
J	0.91	-	0.036	-
K	-	2.36	-	0.092
M	1.22	-	0.048	-